

Foundation Energy Management, LLC
WELLBORE DIAGRAM

Well / Battery	Prospect Name		Total Depth	Current Status
Cure 31-32	Bonny		1850'	Shut in

WELLBORE DIAGRAM

General Info

API #: 05-125-08384

Spud Date:	9/29/2001
Completion Date:	10/13/2001

TVD:	
MD:	1,850
Last PBTD:	1,800

Tubing Detail

2 3/8	inch(OD)
	# (weight)
1686	depth

Rod Detail

5/8	inch(OD)
	# (weight)
66	Joints

Surface Casing

7	inch (OD)
16	# (weight)
	grade
345	depth from KB
Surface	cement top
125	sacks of cement
9 .875	inch (OD) HOLE SIZE

Production Casing

4 .5	inch (OD)
10.5	# (weight)
	grade
1842	depth from KB
1050	cement top
75	sacks of cement
6 1/4	inch (OD) HOLE SIZE

TOC: 1050'

NBRR
1634'-1597'

Well Notes:

Foundation Energy Management, LLC

WELLBORE DIAGRAM

Well / Battery	Prospect Name		Total Depth	Current Status
Cure 31-32	Bonny		1850'	Shut in

WELLBORE DIAGRAM

General Info

API #: 05-125-08384

Spud Date: 9/29/2001

Completion Date: 10/13/2001

TVD: 1,850

MD: 1,850

Last PBTD: 1,800

Tubing Detail

inch(OD)

(weight)

depth

Rod Detail

50' surf plug w 20sx

Perf and sqz 395-295 w 55sx

TOC: 1050'

2 sx cmt

Set CIBR @ 1547'

NBRR 1634'-1597'

Surface Casing

7 inch (OD)

16 # (weight)

grade

345 depth from KB

Surface cement top

125 sacks of cement

9 .875 inch (OD) HOLE SIZE

Production Casing

4 .5 inch (OD)

10.5 # (weight)

grade

1842 depth from KB

1050 cement top

75 sacks of cement

6 1/4 inch (OD) HOLE SIZE

Well Notes: