
Main Pass
Recorded Mode: 2 MHz Phased Array Multi-Pulse Pitch-Catch
Sensor Offset (in.): 0.5
Scan Resolution (in.): 0.1
Scan Direction: Pipe Movement: Away
Circumferential Resolution (in.): 0.5
Calibration Blocks: Tool Vendor Cal Block
Transducer Frequency: 2 MHz
Transducer Type: Phased Array Multi-Pulse Pitch-Catch
Couplant: Ultrasonic Gel
Couplant Delivery: Squirter
Tool Vendor: Pipeline Integrity Solutions
Tool Model: PIS-UT-2000
Tool Serial Number: 2000-0042
Tool Length (in.): 48
Tool Weight (lb): 35
Min Pipe ID (in.): 11.75
Max Pipe ID (in.): 12.25
Min Wall Thickness (in.): 0.25
Max Wall Thickness (in.): 0.5
Max Pressure (psi): 1500
Max Temperature (°F): 120
Min Temperature (°F): 32
Max Speed (ft/s): 3
Min Speed (ft/s): 0.5
Data Acquisition Rate (Hz): 1000
Number of Channels: 128
Number of Beams: 64
Beam Steering Angle (°): 0
Beam Focus Depth (in.): 0.5
Beam Width (°): 10
Gain (dB): 40
Pulse Width (ns): 100
Pulse Repetition Frequency (Hz): 1000
Receiver Bandwidth (MHz): 1
Receiver Gain (dB): 40
Receiver Filter: Low Pass
Receiver Filter Frequency (MHz): 1
Receiver Filter Order: 4
Receiver Filter Type: Butterworth
Receiver Filter Ripple (dB): 0.5
Receiver Filter Stopband Attenuation (dB): 40
Receiver Filter Passband Ripple (dB): 0.5
Receiver Filter Stopband Ripple (dB): 40
Receiver Filter Passband Attenuation (dB): 0.5
Receiver Filter Stopband Frequency (MHz): 1.5
Receiver Filter Passband Frequency (MHz): 1
Receiver Filter Transition Bandwidth (MHz): 0.5
Receiver Filter Transition Frequency (MHz): 1.25
Receiver Filter Transition Attenuation (dB): 20
Receiver Filter Transition Ripple (dB): 20
Receiver Filter Transition Order: 2
Receiver Filter Transition Type: Butterworth
Receiver Filter Transition Passband Ripple (dB): 0.5
Receiver Filter Transition Stopband Ripple (dB): 40
Receiver Filter Transition Passband Attenuation (dB): 0.5
Receiver Filter Transition Stopband Frequency (MHz): 1.5
Receiver Filter Transition


Physical Plans
Benchmark TPC-H 1TB Parquet Dataset Physical Plans
Physical Plan
Physical Plan
Physical Plan

0	(degF)	20

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb)
			Titan CHD-14375 GO Titan 1-7/16" Assembled Electric Cable Head with 1" Fishing Neck	1.03	1.44	3.60
			BTA-MUD BTA 2-3/4" Roller 6 Arm Centralizer with Reversible Ends	2.92	2.72	25.00
TEMP	14.19					
			Probe Radii-2750 RBT (FW1305-098) Probe 2-3/4" Radial Cement Bond Tool with Integral Temperature Sub	9.39	2.75	105.00
WVFS8	11.96					
WVFS7	11.96					
WVFS6	11.96					
WVFS5	11.96					
WVFS4	11.96					
WVFS3	11.96					
WVFS2	11.96					
WVFS1	11.96					
WVFCAL	11.96					
WVF3FT	11.96					
WVF5FT	10.96					
			BTA-MUD BTA 2-3/4" Roller 6 Arm Centralizer with Reversible Ends	2.92	2.72	25.00
CCL	3.88					
			Probe GR-CCL ANL-2750 A (FW1305-083) Probe 2.75" Analog 4 Channel Pulse Gamma Ray/CCL Combined	4.54	2.75	55.00
GR	1.14					
			GO BN-14375 GO 1-7/16" Bull Nose with Go Box Top	0.25	1.44	1.00

Dataset: tep_chevron gm 43-19_rbl_02-03-21.db: field/well/run1/main.1
Total length: 21.05 ft
Total weight: 214.60 lb
O.D.: 2.75 in

Calibration Report

Database File: c:\programdata\warrior\data\tep\tep_chevron gm 43-19_rbl_02-03-21\tep_chevron gm 43-19_rbl_02-03-21.d
Dataset Pathname: main.1
Dataset Creation: Thu Feb 04 12:43:14 2021

Gamma Ray Calibration Report

Serial Number:	FW1305-083	
Tool Model:	2750 A	
Performed:	Sun Nov 12 05:37:57 2017	
Calibrator Value:	637.0	GAPI
Background Reading:	95.7	cps
Calibrator Reading:	982.0	cps
Sensitivity:	0.7188	GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	FW1305-098	
Tool Model:	2750 RBT	
Calibration Casing Diameter:	4.500	in
Calibration Depth:	30.128	ft

Master Calibration, performed (Derived):

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.010	0.778	0.800	81.196	104.664	-0.248
CAL	0.004	0.760				
5'	0.015	0.699	0.800	81.196	117.522	-0.993
SUM						
S1	0.016	0.702	0.000	100.000	145.789	-2.340
S2	0.016	0.786	0.000	100.000	129.825	-2.079
S3	0.012	0.863	0.000	100.000	117.527	-1.402
S4	0.011	0.864	0.000	100.000	117.265	-1.343
S5	0.015	0.816	0.000	100.000	124.841	-1.862
S6	0.015	0.773	0.000	100.000	131.928	-1.949
S7	0.012	0.719	0.000	100.000	141.328	-1.675
S8	0.013	0.684	0.000	100.000	148.847	-1.873

Internal Reference Calibration, performed (Not Performed):

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.004	0.760	1.000	0.000

Air Zero Calibration, performed Wed Feb 3 09:23:21 2021:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Temperature Calibration Report

Serial Number:	FW1305-098	
Tool Model:	2750 RBT	
Performed:	Mon Oct 1 11:32:17 2018	
	Reference	Reading
Low Reference:	100.00 degF	109.43 degF
High Reference:	350.00 degF	405.87 degF
Gain:	0.84	
Offset:	7.72	
Delta Spacing	1	

RELIANCE WELLFIELD SERVICES

Company	TEP Rocky Mountain LLC
Well	Chevron GM 43-19
Field	Grand Valley
County	Garfield
State	Colorado