



Terra Energy Partners, LLP

Garfield County, CO
Sec 20, T6S, R96W
CHEVRON GM 43-19
Wellbore #1

Design: Wellbore #1

QES Survey Certification Report

19 January, 2021



Quintana Energy Services

11390 FM 830
Willis, TX 77318
Phone: (936) 856-4332
Fax: (936) 856-8678

**Survey Certification Sheet**

Company	Job Number	Date
Terra Energy Partners, LLP	RM-200854	01/19/2021

Lease	Well Name	County & State
SWNW 20 6S96W 6PM	GM 43-19	Garfield County, CO

API No.	Survey Depth Range	Survey Type
05-045-24357	383 feet to 7395 feet MD	MWD

Sidetrack Information	Directional Supervisor/Surveyor
Click here to enter text.	Richie Moulton

Certification Statement

The data and calculations for this survey have been checked by me and conform to the standards and procedures set forth by Quintana Energy Services (QES). This report represents a true and correct directional survey of this well based on the original data obtained at the well site. Wellbore coordinates are calculated using minimum curvature.

Kristopher
Ray

Kristopher Ray

Regulatory Compliance Manager

Quintana Energy Services

A red digital signature of the name "Kristopher Ray" is overlaid on the page, positioned between the handwritten-style name and the electronic signature text.

Digitally signed by Kristopher Ray
DN: cn=Kristopher Ray, o, ou,
email=kris.ray@klxenergy.com,
c=US
Date: 2021.01.27 09:30:45 -06'00'



QES
QES Survey Certification Report



Company:	Terra Energy Partners, LLP	Local Co-ordinate Reference:	Well GM 43-19				
Project:	Garfield County, CO	TVD Reference:	KB=24' @ 5771.50usft (H&P #318)				
Site:	Sec 20, T6S, R96W	MD Reference:	KB=24' @ 5771.50usft (H&P #318)				
Well:	GM 43-19	North Reference:	True				
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature				
Design:	Wellbore #1	Database:	EDM 5000.1 Single User Db				
Project	Garfield County, CO						
Map System:	US State Plane 1983	System Datum:	Mean Sea Level				
Geo Datum:	North American Datum 1983						
Map Zone:	Colorado Central Zone						
Site	Sec 20, T6S, R96W						
Site Position:		Northing:	1,622,121.83 usft 39.511803				
From:	Map	Easting:	2,255,366.39 usft -108.139633				
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16" -1.66 °				
Well	GM 43-19						
Well Position	+N/S +E/W	0.00 usft Northing: Easting:	1,622,108.23 usft 2,255,409.28 usft				
Position Uncertainty	0.00 usft	Wellhead Elevation:	usft				
			Latitude: Longitude: Grid Convergence:				
Wellbore	Wellbore #1						
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)		
	HDGM2020	12/7/2020	9.33	65.73	51,360.50000000		
Design	Wellbore #1						
Audit Notes:							
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.00		
Vertical Section:		Depth From (TVD) (usft)	+N/S (usft)	+E/W (usft)	Direction (°)		
		0.00	0.00	0.00	227.51		
Survey Program	Date	1/19/2021					
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description			
383.00	7,395.00	QES MWD Surveys (Wellbore #1)	OWSG (REV5) MWD HDGM OWSG MWD - Standard				
Survey							
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
383.00	1.76	84.56	382.94	0.56	5.86	5.88	84.56
First MWD Survey @ 383.00' MD / 382.94' TVD							
474.00	0.40	249.97	473.93	0.58	6.95	6.97	85.22
564.00	3.65	239.08	563.86	-1.00	4.19	4.31	103.39
655.00	6.99	233.45	654.46	-5.79	-2.74	6.40	205.34
746.00	10.90	228.70	744.33	-14.77	-13.66	20.11	222.77
835.00	15.56	222.90	830.95	-29.07	-28.11	40.44	224.04
927.00	19.56	220.27	918.65	-49.87	-46.47	68.17	222.98
1,059.00	22.98	224.34	1,041.64	-85.17	-78.78	116.02	222.77
1,153.00	25.88	229.52	1,127.23	-111.62	-107.22	154.77	223.85
1,247.00	29.05	231.90	1,210.63	-139.03	-140.79	197.87	225.36

Company:	Terra Energy Partners, LLP	Local Co-ordinate Reference:	Well GM 43-19
Project:	Garfield County, CO	TVD Reference:	KB=24' @ 5771.50usft (H&P #318)
Site:	Sec 20, T6S, R96W	MD Reference:	KB=24' @ 5771.50usft (H&P #318)
Well:	GM 43-19	North Reference:	True
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Wellbore #1	Database:	EDM 5000.1 Single User Db

Survey								
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)	
1,341.00	33.18	229.96	1,291.09	-169.67	-178.46	246.24	226.45	
1,435.00	38.06	229.00	1,367.48	-205.25	-220.04	300.91	226.99	
1,529.00	42.32	228.21	1,439.27	-245.37	-265.53	361.54	227.26	
1,623.00	42.41	231.55	1,508.73	-286.17	-313.95	424.80	227.65	
1,717.00	42.06	230.84	1,578.33	-325.76	-363.19	487.88	228.11	
1,811.00	41.22	230.84	1,648.58	-365.21	-411.62	550.28	228.42	
1,905.00	41.92	229.88	1,718.90	-405.00	-459.64	612.62	228.62	
1,999.00	41.62	229.88	1,789.01	-445.35	-507.53	675.22	228.73	
2,092.00	41.31	229.00	1,858.70	-485.39	-554.31	736.79	228.79	
2,186.00	40.34	227.77	1,929.83	-526.19	-600.26	798.24	228.76	
2,279.00	38.67	227.15	2,001.59	-566.19	-643.85	857.39	228.67	
2,373.00	39.64	227.41	2,074.48	-606.45	-687.46	916.72	228.58	
2,466.00	39.16	227.59	2,146.34	-646.33	-730.98	975.74	228.52	
2,561.00	39.20	226.89	2,219.98	-687.08	-775.04	1,035.74	228.44	
2,655.00	39.29	227.06	2,292.78	-727.66	-818.52	1,095.19	228.36	
2,749.00	38.06	226.97	2,366.16	-767.70	-861.49	1,153.92	228.29	
2,844.00	38.72	226.45	2,440.63	-808.16	-904.43	1,212.89	228.22	
2,938.00	36.61	226.01	2,515.03	-847.89	-945.91	1,270.29	228.13	
3,032.00	33.84	226.18	2,591.81	-885.48	-984.96	1,324.47	228.04	
3,127.00	31.82	225.48	2,671.63	-921.36	-1,021.91	1,375.94	227.96	
3,221.00	31.03	226.62	2,751.85	-955.38	-1,057.19	1,424.92	227.90	
3,315.00	30.54	226.71	2,832.60	-988.39	-1,092.18	1,473.02	227.86	
3,410.00	30.01	227.33	2,914.65	-1,021.05	-1,127.22	1,520.91	227.83	
3,504.00	27.91	228.12	2,996.89	-1,051.67	-1,160.89	1,566.42	227.83	
3,598.00	25.80	228.38	3,080.74	-1,079.95	-1,192.56	1,608.88	227.84	
3,692.00	23.82	228.65	3,166.06	-1,106.08	-1,222.11	1,648.32	227.85	
3,786.00	23.25	229.00	3,252.24	-1,130.79	-1,250.36	1,685.85	227.87	
3,880.00	21.01	230.23	3,339.32	-1,153.74	-1,277.32	1,721.24	227.91	
3,974.00	19.78	228.29	3,427.42	-1,175.11	-1,302.14	1,753.98	227.94	
4,068.00	18.28	226.54	3,516.28	-1,195.83	-1,324.72	1,784.63	227.93	
4,162.00	16.35	227.50	3,606.02	-1,214.91	-1,345.18	1,812.60	227.91	
4,256.00	14.55	227.50	3,696.62	-1,231.83	-1,363.64	1,837.64	227.91	
4,350.00	12.57	229.00	3,787.99	-1,246.52	-1,380.06	1,859.67	227.91	
4,444.00	11.47	225.83	3,879.93	-1,259.74	-1,394.49	1,879.24	227.91	
4,539.00	10.06	225.83	3,973.26	-1,272.10	-1,407.22	1,896.97	227.89	
4,633.00	8.70	226.97	4,066.00	-1,282.68	-1,418.30	1,912.29	227.87	
4,727.00	7.03	227.59	4,159.11	-1,291.41	-1,427.75	1,925.15	227.87	
4,821.00	5.36	227.41	4,252.56	-1,298.26	-1,435.23	1,935.29	227.87	
4,915.00	2.86	221.70	4,346.31	-1,302.98	-1,440.02	1,942.01	227.86	
5,009.00	1.54	181.18	4,440.24	-1,306.00	-1,441.61	1,945.21	227.83	
5,103.00	0.66	151.56	4,534.23	-1,307.74	-1,441.37	1,946.21	227.78	
5,197.00	0.88	121.68	4,628.22	-1,308.59	-1,440.50	1,946.14	227.75	
5,291.00	0.70	128.98	4,722.21	-1,309.33	-1,439.44	1,945.85	227.71	
5,385.00	1.10	115.79	4,816.20	-1,310.08	-1,438.18	1,945.43	227.67	

Company:	Terra Energy Partners, LLP	Local Co-ordinate Reference:	Well GM 43-19
Project:	Garfield County, CO	TVD Reference:	KB=24' @ 5771.50usft (H&P #318)
Site:	Sec 20, T6S, R96W	MD Reference:	KB=24' @ 5771.50usft (H&P #318)
Well:	GM 43-19	North Reference:	True
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Wellbore #1	Database:	EDM 5000.1 Single User Db

Survey								
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)	
5,480.00	1.01	127.92	4,911.18	-1,311.00	-1,436.70	1,944.95	227.62	
5,573.00	0.66	145.85	5,004.17	-1,311.94	-1,435.75	1,944.89	227.58	
5,667.00	0.44	196.92	5,098.17	-1,312.74	-1,435.55	1,945.27	227.56	
5,761.00	0.83	212.65	5,192.16	-1,313.65	-1,436.03	1,946.24	227.55	
5,855.00	1.01	213.18	5,286.15	-1,314.92	-1,436.85	1,947.70	227.54	
5,949.00	1.40	213.64	5,380.13	-1,316.57	-1,437.94	1,949.62	227.52	
6,043.00	1.19	211.68	5,474.11	-1,318.36	-1,439.09	1,951.67	227.51	
6,137.00	1.14	214.41	5,568.09	-1,319.96	-1,440.13	1,953.52	227.49	
6,231.00	1.32	224.78	5,662.06	-1,321.50	-1,441.42	1,955.52	227.49	
6,326.00	1.63	221.61	5,757.03	-1,323.29	-1,443.09	1,957.95	227.48	
6,420.00	2.11	225.92	5,850.98	-1,325.49	-1,445.22	1,961.01	227.47	
6,514.00	2.37	228.91	5,944.91	-1,327.97	-1,447.93	1,964.69	227.47	
6,608.00	2.50	237.26	6,038.83	-1,330.36	-1,451.11	1,968.65	227.49	
6,702.00	3.03	234.97	6,132.72	-1,332.89	-1,454.87	1,973.13	227.51	
6,796.00	3.12	236.38	6,226.58	-1,335.73	-1,459.04	1,978.12	227.53	
6,890.00	3.74	226.36	6,320.41	-1,339.27	-1,463.39	1,983.72	227.54	
6,983.00	3.78	226.80	6,413.21	-1,343.46	-1,467.82	1,989.82	227.53	
7,078.00	4.70	234.27	6,507.95	-1,347.88	-1,473.26	1,996.81	227.54	
7,172.00	5.23	231.72	6,601.60	-1,352.78	-1,479.75	2,004.91	227.57	
7,266.00	5.58	229.88	6,695.18	-1,358.38	-1,486.61	2,013.75	227.58	
7,322.00	5.71	229.71	6,750.91	-1,361.93	-1,490.81	2,019.25	227.59	
7,395.00	5.71	229.71	6,823.55	-1,366.63	-1,496.35	2,026.51	227.59	

Projection to TD @ 7395.00' MD / 6823.55' TVD

Design Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment	
		+N/-S (usft)	+E/-W (usft)		
383.00	382.94	0.56	5.86	First MWD Survey @ 383.00' MD / 382.94' TVD	
7,395.00	6,823.55	-1,366.63	-1,496.35	Projection to TD @ 7395.00' MD / 6823.55' TVD	

Checked By: _____ Approved By: _____ Date: _____