RELIANCE OILFIELD SERVICES

Radial Cement Bond
Gamma Ray
Casing Collar Log

Company	TEP Rocky Mountain LLC
Well	Chevron GM 332-19
Field	Grand Valley
County	Garfield
State	Colorado

Company TEP Rocky Mountain LLC
Well Chevron GM 332-19
Field Grand Valley
County Garfield State Colorado
Location: API #: 05-045-24362
SEC 20 TWP 6S RGE 96W
Other Services ---

Permanent Datum	Ground Level	Elevation 5752.1'	Elevation
Log Measured From	Kelly Bushing	24 FT	K.B. 5776.1'
Drilling Measured From	Kelly Bushing		D.F. ---
			G.L. 5752.1'

Date	03-FEB-2021
Run Number	One
Depth Driller	7777 FT
Depth Logger	7720 FT
Bottom Logged Interval	7708 FT
Top Log Interval	Surface
Open Hole Size	8.750"
Type Fluid	Water
Density / Viscosity	8.34 lb/gal
Max. Recorded Temp.	227°F
Estimated Cement Top	See Log
Time Well Ready	ROA
Time Logger on Bottom	6:00
Equipment Number	HD-0331
Location	Grand Junction, CO
Recorded By	Z. Fisher
Witnessed By	---

Borehole Record				Tubing Record			
Run Number	Bit	From	To	Size	Weight	From	To

Casing Record	Size (in)	Wgt (lbs/Ft)	Grade	Top	Bottom
Surface Casing	9 5/8	36	J-55	Surface	1028 FT
Intermediate #1	4 1/2	11.6	P-110	Surface	7734 FT
Intermediate #2					
Liner					

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Log ran as per customer request
Depth referenced to Kelly Bushing at 24 FT
Marker Joint logged from 4713 - 4734 FT
Recorded with 0 PSI Surface Induced Pressure

Thank you for choosing Reliance Oilfield Services, LLC!

RELIANCE OILFIELD SERVICES

Main Pass

Recorded With 0 PSI Surface Induced Pressure

Database File	tep\tep_chevron gm 332-19_rbl_02-03-21\tep_chevron gm 332-19_rbl_02-03-21.db
Dataset Pathname	main.2
Presentation Format	ros_radii_tep
Dataset Creation	Fri Feb 05 17:00:02 2021
Charted by	Depth in Feet scaled 1:240

Gamma Ray
0 (GAPI) 200
Casing Collar Locator
Line Speed
-150 (ft/min) 150
Line Tension
0 (lb) 2000
Differential Temperature
-2 (degF) 2
Temperature
0 (degF) 20

3' Amplitude
0 (mV) 100
3' Amplitude x 5
0 (mV) 20
3' Travel Time
300 (usec) 200

5' Variable Density Log
200 (usec) 1200

Sector Map

Average Amplitude
0 150
Mimimum Amplitude
0 150
Maximum Amplitude
0 150


144.3
3800
146.1
3900


148.0
4000
149.9
4100


151.7
4200
153.7
4300


155.7
4400
157.7
4500


159.9
4600
162.0
4700
Marker Joint


163.8
4800
165.2
4900
166.8
5000


168.7
5100
170.3
5200


172.3
5300
174.2
5400


175.9
5500
177.9
5600


179.6
5700
181.6
5800


183.4
5900
185.1
6000


186.9
6100
188.6
6200


190.4
6300
192.4
6400


194.4
6500
196.3
6600


198.1
6700
200.1
6800


202.3
6900
204.1
7000


206.3
7100
208.4
7200


211.6
7300
214.6
7400


219.5
7500
224.0
7600
LTEN
LSPD
CCL
GR
t (°F)
dt(°F)
t (°F)
227.0
7700
3' Amp
3' TT
3' Ampx5
Sectors



Gamma Ray 0 (GAPI) 200 Casing Collar Locator Line Speed -150 (ft/min) 150 Line Tension 0 (lb) 2000 Differential Temperature -2 (degF) 2 Temperature 0 (degF) 20	3' Amplitude 0 (mV) 100 3' Amplitude x 5 0 (mV) 20 3' Travel Time 300 (usec) 200	5' Variable Density Log 200 (usec) 1200	Sector Map	Average Amplitude 0 150 MimimumAmplitude 0 150 MaximumAmplitude 0 150

RELIANCE OILFIELD SERVICES

Repeat Pass

Recorded With 0 PSI Surface Induced Pressure

Database File	tep\tep_chevron gm 332-19_rbl_02-03-21\tep_chevron gm 332-19_rbl_02-03-21.db
Dataset Pathname	repeat.4
Presentation Format	ros_radii_tep
Dataset Creation	Sat Feb 06 11:58:14 2021
Charted by	Depth in Feet scaled 1:240

Gamma Ray 0 (GAPI) 200 Line Speed -150 (ft/min) 150 Line Tension 0 (lb) 2000 Differential Temperature -2 (degF) 2 Temperature 0 (degF) 20	3' Amplitude 0 (mV) 100 3' Amplitude x 5 0 (mV) 20 3' Travel Time 300 (usec) 200	5' Variable Density Log 200 (usec) 1200	Sector Map	Average Amplitude 0 150 MimimumAmplitude 0 150 MaximumAmplitude 0 150



Gamma Ray 0 (GAPI) 200 Line Speed -150 (ft/min) 150 Line Tension 0 (lb) 2000 Differential Temperature -2 (degF) 2 Temperature 0 (degF) 20	3' Amplitude 0 (mV) 100 3' Amplitude x 5 0 (mV) 20 3' Travel Time 300 (usec) 200	5' Variable Density Log 200 (usec) 1200	Sector Map	Average Amplitude 0 150 MimimumAmplitude 0 150 MaximumAmplitude 0 150

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb
			Titan CHD-14375 GO Titan 1-7/16" Assembled Electric Cable Head with 1" Fishing Neck	1.03	1.44	3.60
			BTA-MUD BTA 2-3/4" Roller 6 Arm Centralizer with Reversible Ends	2.92	2.72	25.00
TEMP	14.19					
			Probe Radii-2750 RBT (ROFS-RBT-0001) Probe 2-3/4" Radial Cement Bond Tool with Integral Temperature Sub	9.39	2.75	105.00
WVFS8	11.96					
WVFS6	11.96					
WVFS5	11.96					
WVFS7	11.96					
WVFS4	11.96					
WVFS3	11.96					
WVFS2	11.96					
WVFS1	11.96					
WVFCAL	11.96					
WVF3FT	11.96					
WVF5FT	10.96					
			BTA-MUD BTA 2-3/4" Roller 6 Arm Centralizer with Reversible Ends	2.92	2.72	25.00
CCL	3.88					
			Probe GR-CCL ANL-2750 A (FW1305-083) Probe 2.75" Analog 4 Channel Pulse Gamma Ray/CCL Combined	4.54	2.75	55.00
GR	1.14					
			GO BN-14375 GO 1-7/16" Bull Nose with Go Box Top	0.25	1.44	1.00

Dataset:	tep_chevron gm 332-19_rbl_02-03-21.db: field/well/run1/main.2
Total length:	21.05 ft
Total weight:	214.60 lb
O.D.:	2.75 in

Calibration Report

Database File	c:\programdata\warrior\data\tep\tep_chevron gm 332-19_rbl_02-03-21\tep_chevron gm 332-19_rbl_02-03-2
Dataset Pathname	main.2
Dataset Creation	Fri Feb 05 17:00:02 2021

Gamma Ray Calibration Report

Serial Number:	FW1305-083	
Tool Model:	2750 A	
Performed:	Sun Nov 12 05:37:57 2017	
Calibrator Value:	637.0	GAPI
Background Reading:	95.7	cps
Calibrator Reading:	982.0	cps
Sensitivity:	0.7188	GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	ROFS-RBT-0001	
Tool Model:	2750 RBT	
Calibration Casing Diameter:	4.500	in
Calibration Depth:	30.987	ft

Master Calibration, performed (Derived):

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.006	0.652	0.800	81.196	124.425	0.105
CAL	0.003	0.767				
5'	0.007	0.645	0.800	81.196	125.879	-0.029
SUM						
S1	0.006	0.729	0.000	100.000	138.373	-0.825
S2	0.006	0.704	0.000	100.000	143.270	-0.899
S3	0.006	0.729	0.000	100.000	138.254	-0.851
S4	0.006	0.688	0.000	100.000	146.728	-0.928
S5	0.006	0.688	0.000	100.000	146.728	-0.928
S6	0.006	0.675	0.000	100.000	149.567	-0.897
S7	0.006	0.675	0.000	100.000	149.567	-0.897
S8	0.006	0.706	0.000	100.000	142.901	-0.820

Internal Reference Calibration, performed (Not Performed):

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.003	0.767	1.000	0.000

Air Zero Calibration, performed Tue Feb 2 10:16:50 2021:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Temperature Calibration Report

Serial Number:	ROFS-RBT-0001	
Tool Model:	2750 RBT	
Performed:	Mon Oct 1 11:32:12 2018	
	Reference	Reading
Low Reference:	100.00 degF	112.12 degF
High Reference:	350.00 degF	415.62 degF
Gain:	0.82	
Offset:	7.65	
Delta Spacing	1	

RELIANCE OILFIELD SERVICES

Company	TEP Rocky Mountain LLC
Well	Chevron GM 332-19
Field	Grand Valley
County	Garfield
State	Colorado