

CNTY:	<u>Weld</u>	FTG:	<u>660 FNL and 1968 FWL</u>	IP GAS:	<u>0</u>
STATE:	<u>CO</u>	Q-Q:	<u>NENW</u>	IP OIL:	<u>0</u>
ROTARY SPUD:	<u>25-Jun-90</u>	SEC.:	<u>13</u>	IP WTR:	<u>0</u>
COMP/PA:	<u>2-Jul-90</u>	TWS:	<u>7N</u>	CUM GAS:	<u>0</u>
STATUS:	<u>DA</u>	RGE:	<u>59W</u>	CUM OIL:	<u>0</u>
WBD DATE:	<u>31-Aug-21</u>	BY:	<u>SMB</u>	CUM WTR:	<u>0</u>
LAT/LONG:	<u>40.580176/-103.928337</u>			LAST PROD:	<u>n/a</u>

CURRENT WELLBORE DIAGRAM

KBE:	<u>4896</u>	'
KB:	<u>8</u>	'
GLE:	4888	'

WCR 119 & Hwy 14. S 2.1. E 0.4 Into.

Weld on Plate

Plug #3

TD (ft): 6725 '
PBTD (ft): 0 '

CASING HEAD: [None](#)
WELLHEAD: [None](#)

CASING RECORD

HOLE (in)	SIZE (in)	WT (lb/ft)	GRADE	TOP (ft)	BTM (ft)	JTS
12 1/4	8 5/8	24		0	373	

Float Collar @

TUBING RECORD

COND: DATE:

<u>SIZE (in)</u>	<u>WT (lb/ft)</u>	<u>GRADE</u>	<u>TOP (ft)</u>	<u>TALLY (ft)</u>	<u>JTS</u>

8 5/8" 24# Csg @ 373'
w/ 350 sxs

Plug #2

ITEM	DESC	SIZE (in)	TALLY (ft)	JTS

Top White River	@	0'
Base White River	@	80'
Top Laramie-Fox Hills	@	80'
Base Laramie-Fox Hills	@	360'
Top Pierre Shale	@	360'
Base Pierre Shale	@	680'
Top Upper Pierre	@	680'
Base Upper Pierre	@	1475'
Top Parkman	@	3090'
Top Niobrara	@	5840'
Top D Sand	@	6532'
Top J Sand	@	6621'

PERFORATION RECORD

[illegible]

WELLWORK HISTORY

DA since 1990

Plug 1 = 35 sx from 6550' to 6430'

Plug 2 = 30 sx from 400' to 318

Plug 3 = 10 sx from 66' to 10'

Plug #1

OPEN HOLE

TD @ 6725 '
7-7/8" Hole