



P&A Wellbore For State

Well Name: SCHMIDT 25-08F

Land, Original Hole, 6/6/2022 8:35:56 AM		Well Header									
MD (ftKB)	Vertical schematic (actual)	Surface UWI 0512316146			Business Unit Rockies			Gov Auth Dist		Prod Tree Loc Land	
		Orig. KB to Gnd (ft) 12.00		Original Spud Date 9/29/1992		Abandon Date		Well Sub-Status TA			High... N
Comment DISCREPANCY: DRILL & COMPLETE FGS DATE- ST 11/6/92, DRL RPTS 11/4/92.											
Surface Location (Congressional)											
Qtr 3 SE		Qtr 4 NE	Section 25	Twnshp 4	Twnsh... N	Range 66	Rng E/... W	Latitude (°) 40.28509581 5	Longitude (°) -104.717515908		
Wellbore Sections											
Section Des			Hole Size (in)			Act Top (ftKB)		Act Btm (ftKB)			
SURFACE			12 1/4			12.0		520.0			
PRODUCTION			7 7/8			520.0		7,365.0			
Casing Strings											
Csg Des			Run Date		OD (in)	Wt/Len (lb/ft)	Grade	Top Depth (MD) (ftKB)	Set Depth (MD) (ftKB)		
Surface			9/29/1992		8 5/8	23.00	WC-50	12	516		
Production Casing			10/5/1992		4 1/2	11.60	M-75	12	7352		
Cement											
Des					Start Date		Top (ftKB)		Btm (ftKB)		
SURFACE CASING CEMENT					9/29/1992		12.0		516.0		
PRODUCTION CASING CEMENT					10/5/1992		2,940.0		3,994.0		
PRODUCTION CASING CEMENT					10/5/1992		6,654.0		7,352.0		
Balance Plug					5/12/2022		6,853.3		7,220.3		
Zone Statuses											
Zone Name		Status Date	Status	Fluid Type	Job				Prod Method		
CODELL		1/29/2010	PR						Flowing		
CODELL		5/12/2022	TA		SET CEMENT PLUG, 5/11/2022 00:00						
Perforation Data											
Linked Zone			Explosive Type	Entered Shot Total	Top (ftKB)		Btm (ftKB)		Date		
CODELL, Original Hole				56	7,240.0		7,254.0		1/24/2000		
CODELL, Original Hole				52	7,242.0		7,254.0		2/12/2003		
CODELL, Original Hole				20	7,242.0		7,252.0		10/11/1992		
Stimulation Intervals											
Zone				Start Date		Top (ftKB)		Btm (ftKB)			
CODELL, Original Hole				2/4/2000		7,240.0		7,254.0			
CODELL, Original Hole				10/13/1992		7,242.0		7,252.0			
CODELL, Original Hole				2/25/2003		7,242.0		7,254.0			
				2/20/2003							
Other In Hole											
Run Date		Des			Make		OD (in)	Top (ftKB)	Btm (ftKB)		
Logs											
Date		Type					Depth Top (MD) (ftKB)	Btm (ftKB)			
10/4/1992		COMPENSATED DENSITY					3,650	7,326.0			
10/4/1992		INDUCTION					516	7,363.0			
10/9/1992		CEMENT BOND					2,648	7,214.0			
3/7/2013		GYRO					12	7,200.0			
Plug Back Total Depths											
Date		Type		Com					PBSD (ftKB)		
3/20/2014		FILL							7,308		
5/11/2022		FILL							7,331		

MD (ftKB)

Vertical schematic (actual)

12.1

263.3

514.4

515.3

516.1

518.0

520.0

1,730.0

2,940.0

3,467.0

3,994.1

5,324.0

6,653.9

6,753.6

6,853.3

7,036.1

7,218.8

7,219.3

7,219.8

7,220.0

7,220.1

7,230.2

7,240.2

7,241.1

7,242.1

7,247.0

7,252.0

7,253.0

7,253.9

7,280.0

7,306.1

7,318.6

7,331.0

7,340.7

7,350.4

7,351.2

7,352.0

7,358.6

7,365.2

7,720.1

SURFACE CASING CEMENT; 12-516; 9/29/1992

PRODUCTION CASING CEMENT; 2940-3994; 10/5/1992; LEAD NO CMT FROM 6654' - 4000' (GEL SPACER)

Balance Plug; 6853.3-7220.3; 5/12/2022; 25 SKS 5.13 BBLS 15.8 PPG G NEAT CEMENT WITH RETARDER PRODUCTION CASING CEMENT; 6654-7352; 10/5/1992; TAIL

Perforated; 7240-7254; 1/24/2000; Perf

Perforated; 7242-7252; 10/11/1992; Perf

Perforated; 7242-7254; 2/12/2003; Perf