

PLUGGING RECORD

RECEIVED
NOV 17 1960
OIL & GAS
CONSERVATION COMMISSION

Within thirty (30) days after the plugging of any well, the owner or operator thereof shall file this form in duplicate for wells on Patented or Federal lands, and in triplicate for wells on State lands, give a detailed account of the manner in which the abandonment or plugging work was carried out, including the nature and quantities of materials used in plugging and the location and extent (by depths) of the plugs of different materials; records of the amount, size and location (by depths) of casings and junk left in the well; and a detailed statement of the volume and weight of mud fluid used.

Operator VINCENT AND WELCH, INC. Field Wildcat X

Lease Name Gorman Well No. 1 County Logan

Location C. W/2 of Lot 2, Section 22, Township 12N, Range 55W, Meridian 6th P.M.
(Quarter Quarter)

295 feet from North Section line and 660 feet from West Section Line
N or S E or W

DATE OF PLUGGING November 10, 1960

The hole was filled with heavy mud from total depth to 240'. A 15 sack cement plug was spotted in and below surface casing from 210' to 240'. Remainder of surface casing was filled with heavy mud, and a 5 sack cement plug was placed in top of surface casing.

AJJ	
DVR	
WRS	
HHM	
JAM	✓
FJP	
JJD	✓
FILE	

Plugging checked on 4/24/61 Jim

I/we hereby swear (or affirm) that the statements herein made are a full and correct report:

Date NOV 17 1960

DON M. ROUNDS DRILLING CO., INC.
 Company (Contractor) Date Nov. 15, 1960
 925 Petroleum Club Bldg.,
 Address Denver 2, Colorado Phone No. MA 3-0296
 By *George Dean* Title Prod. Engineer
 (Signature)

VIOLATION

REMARKS: ^{NO} Approval to plug prior to plug-in.