



## **Terra Energy Partners, LLP**

**Rio Blanco County, CO**

**RG 23-7-297 Pad**

**RG 313-7-297 - Slot RG 313-7-297**

**Wellbore #1**

**Design: Wellbore #1**

## **KLX Survey Certification Report**

**27 August, 2022**



**KLX Directional Drilling, INC.**

11390 FM 830  
Willis, TX 77318  
Phone: (936) 856-4332  
Fax: (936) 856-8678

---

**Survey Certification Sheet**

Company	Job Number	Date
TEP Rocky Mountain LLC	RM-220736	8/27/2022

Lease	Well Name	County & State
15 7 2S97W 6	Federal #RG 313-7-297	Rio Blanco, CO

API No.	Survey Depth Range	Survey Type
05-103-12479	233 feet to 1410 feet MD	MWD

Sidetrack Information	Directional Supervisor/Surveyor
<a href="#">Click here to enter text.</a>	Robert Cuevas

**Certification Statement**

The data and calculations for this survey have been checked by me and conform to the standards and procedures set forth by KLX Directional Drilling. This report represents a true and correct directional survey of this well based on the original data obtained at the well site. Wellbore coordinates are calculated using minimum curvature.

Kristopher Ray  
Regulatory Compliance Manager  
KLX Directional Drilling, Inc.

<b>Company:</b>	Terra Energy Partners, LLP	<b>Local Co-ordinate Reference:</b>	Well RG 313-7-297 - Slot RG 313-7-297
<b>Project:</b>	Rio Blanco County, CO	<b>TVD Reference:</b>	KB=14.5' @ 6617.50usft (Cartel X-15)
<b>Site:</b>	RG 23-7-297 Pad	<b>MD Reference:</b>	KB=14.5' @ 6617.50usft (Cartel X-15)
<b>Well:</b>	RG 313-7-297	<b>North Reference:</b>	True
<b>Wellbore:</b>	Wellbore #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	Wellbore #1	<b>Database:</b>	EDM 5000.1 Single User Db

<b>Project</b>	Rio Blanco County, CO		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	Colorado Central Zone		

Site		RG 23-7-297 Pad			
Site Position:		Northing:	1,760,880.90 usft	Latitude:	39.888499
From:	Map	Easting:	2,206,203.50 usft	Longitude:	-108.329114
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "	Grid Convergence:	-1.78 °

Well	RG 313-7-297 - Slot RG 313-7-297					
Well Position	+N/-S	0.00 usft	Northing:	1,760,889.30 usft	Latitude:	39.888523
	+E/-W	0.00 usft	Easting:	2,206,212.80 usft	Longitude:	-108.329082
Position Uncertainty		0.00 usft	Wellhead Elevation:	usft	Ground Level:	6,603.00 usft

<b>Wellbore</b>	Wellbore #1				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	HDGM2022	8/12/2022	9.18	65.82	51,099.60000000

<b>Design</b>	Wellbore #1				
<b>Audit Notes:</b>					
<b>Version:</b>	1.0	<b>Phase:</b>	ACTUAL	<b>Tie On Depth:</b>	0.00
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>	
	0.00	0.00	0.00	295.34	

<b>Survey Program</b>	<b>Date</b>	8/27/2022			
<b>From (usft)</b>	<b>To (usft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Description</b>	
233.00	1,410.00	KLX MWD Surveys (Wellbore #1)	OWSG (REV5) MWD HDGM	OWSG MWD - Standard	

<b>Survey</b>								
<b>MD (usft)</b>	<b>Inc (°)</b>	<b>Azi (azimuth) (°)</b>	<b>TVD (usft)</b>	<b>N/S (usft)</b>	<b>E/W (usft)</b>	<b>Closure Distance (usft)</b>	<b>Closure Azimuth (°)</b>	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
233.00	1.71	287.17	232.97	1.03	-3.32	3.48	287.17	
<b>First MWD Survey @ 233.00' MD / 232.97' TVD</b>								
325.00	2.90	294.21	324.89	2.39	-6.76	7.16	289.45	
412.00	3.47	294.56	411.75	4.38	-11.16	11.99	291.45	
499.00	4.00	299.39	498.57	6.97	-16.20	17.63	293.27	
587.00	4.66	296.06	586.32	10.04	-22.08	24.26	294.46	
674.00	4.70	291.84	673.03	12.92	-28.57	31.35	294.34	
761.00	5.14	282.78	759.71	15.11	-35.67	38.74	292.95	
848.00	5.41	286.56	846.34	17.14	-43.41	46.67	291.55	
936.00	4.97	297.72	933.98	20.10	-50.76	54.59	291.60	
1,023.00	4.70	305.02	1,020.67	23.89	-57.01	61.82	292.74	

<b>Company:</b>	Terra Energy Partners, LLP	<b>Local Co-ordinate Reference:</b>	Well RG 313-7-297 - Slot RG 313-7-297
<b>Project:</b>	Rio Blanco County, CO	<b>TVD Reference:</b>	KB=14.5' @ 6617.50usft (Cartel X-15)
<b>Site:</b>	RG 23-7-297 Pad	<b>MD Reference:</b>	KB=14.5' @ 6617.50usft (Cartel X-15)
<b>Well:</b>	RG 313-7-297	<b>North Reference:</b>	True
<b>Wellbore:</b>	Wellbore #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	Wellbore #1	<b>Database:</b>	EDM 5000.1 Single User Db

Survey								
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)	
1,110.00	4.57	308.62	1,107.39	28.10	-62.64	68.66	294.16	
1,198.00	5.32	305.20	1,195.06	32.64	-68.71	76.07	295.41	
1,285.00	4.70	295.53	1,281.73	36.50	-75.22	83.61	295.89	
1,329.00	4.04	288.94	1,325.60	37.78	-78.32	86.96	295.76	
1,410.00	4.04	288.94	1,406.40	39.64	-83.72	92.62	295.34	
TD @ 1410.00' MD / 1406.40' TVD								

Design Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment	
		+N/-S (usft)	+E/-W (usft)		
233.00	232.97	1.03	-3.32	First MWD Survey @ 233.00' MD / 232.97' TVD	
1,410.00	1,406.40	39.64	-83.72	TD @ 1410.00' MD / 1406.40' TVD	