



INDUCTION ELECTRICAL LOG

RECEIVED

FOLD HERE The well name, location and borehole reference data were furnished by the customer.

REMARKS:

All interpretations are opinions based on inferences from electrical or other measurements and we cannot, and do not guarantee the accuracy or correctness of any interpretations, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to Clause 7 of our General Terms and Conditions as set out in our current Price Schedule.

SPONTANEOUS-POTENTIAL $-\frac{20}{MV} +$ MILLIVOLTS	DEPTH	6FF40 INDUCTION CONDUCTIVITY	MILLIMHOS/M = $\frac{1000}{OHMS. M^2/M}$
		RESISTIVITY OHMS. M <sup>2</sup> /M AMP. SHORT NORMAL	1000 2000 1000
		SHORT NORMAL A-16"-M	



RESISTIVITY OHMS. M"/M  
AMP. SHORT NORMAL

SHORT NORMAL A-16"-M

6 FF40 INDUCTION

00401818

Casing

0300

0400

0500

0600

0700

0800

Short Normal

Induction Resistivity

Conductivity

SP Curve

Amplified Short Normal