



RECEIVED

AUG 18 1967

COLO. OIL & GAS CONS. COMM.

#3 Harrison

DST

#1 DST 3970-4030 (Marmaton) I.O. 10 min. ISI 45 min. F.O. 105 min. with weak blow increasing to strong blow throughout test. FSI - 105 min.

Rec. 210 ft. of oil and gas cut mud

FP 126-126 SIP 583-953 HP 2008-2033

Coring Record

#1	4726-4749	cut 23'	rec. 13'
#2	4749-4762	cut 13'	rec. 13'
#3	4762-4800	cut 38'	rec. 38'

#3 Harrison

28. Casing Record

5 $\frac{1}{2}$ " csg set at 4825 by squeezing
50 sx cement thru perfs 4810-25 &
50 sx cement thru perfs at 4742 &
50 sx cement thru perfs at 4748 &
175 sx cement thru perfs at 4525

31. Perforation Record

<u>Interval</u>	<u>Size</u>	<u>No.</u>
4810	5/8"	4
4525	5/8"	4
4742	5/8"	4
4648	5/8"	4
4525	5/8"	4
4784-92	0.45"	9
4746-4760	0.45"	15

32. Acid, shot, fracture, Cement Squeeze, etc.

<u>Depth Interval</u>	<u>Amount & Kind of Material Used</u>
4810-25	Squeezed 50 sx of neat cement w/12% NaCl, 2% gel, 1% CFR-2
4742	Squeezed 50 sx of neat cement w/12 $\frac{1}{2}$ % gilsonite, 2% gel, 1% CFR-2 & 12% NaCl
4648	Squeezed with 50 sx of above cement
4525	Squeezed with 125 sx of cement with 12% NaCl, 2% gel & 1% CFR-2 & 50 sx common cement
4784-92	1500 gal 15% MCA
4746-4760	1000 gal 15% MCA