

OFFICE OF STATE OIL INSPECTOR
 SUNDRY NOTICES AND REPORTS OF WELLS
 LOCATED ON PRIVATE LANDS



(Indicate nature of data by checking below)

- Notice of intention to drill.....
- Notice of intention to change plans.....
- Notice of date for test of water shut-off.....
- Report on result of test of water shut-off.....
- Notice of intention to re-drill or repair well.....
- Notice of intention to clean out well.....
- Statement of shooting.....
- Statement of perforating & squeezing.....XXXXXXXXXX
- Notice to pull or otherwise alter casing.....
- Notice of intention to abandon well.....
- Report of work done on well since previous report.....

Following is a ~~(notice on intention to do work)~~ (On land) November 30 1951
 (report of work done) (patented) described as follows:

Colorado Logan Atwood
 State County Field

J-9 Pomeroy 20 SE 1/4 SW 1/4 SE 1/4 T. 7N R. 53W 6th
 (Well No.) (Lease) (Sec. and 1/4 Sec.) (Twp.) (Range) (Meridian)

The well is located 330 ft. (N) of S. Line and 1650 ft. (E) of E Line
 (S) (W)

The elevation above sea level is 4100 (KB) ft.

Details of Plan of Work: (State names of and expected depths to objective sands: Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

The casing was perforated with 2 holes @ 4730-31 (KB) and a drill stem test was taken on 9-29-51. This zone yielded oil and gas and water, so the holes were squeezed with 60 sacks and 50 sacks were put away with a maximum pressure 2500 psi. After 36 hours the hole was then cleaned out to 4727 and the zone from 4721-26 was perforated with 4 holes per foot. A test of this zone yielded an estimated 1.5 MMCF of gas with oil and water, so it was squeezed with 60 sacks. A total of 18 sacks were put away with a maximum pressure of 3000 psi. The cement was allowed to set for 36 hours at which time the zone from 4712-13 was perforated with 2 holes. These holes were squeezed, putting away 17 sacks under a maximum pressure of 2500 psi. After 36 hours, the hole was cleaned out to 4733 (KB). Two holes were shot in the casing @ 4730-31. A drill stem test was taken of the holes with 15' of drilling mud recovered in a one hour test.

The zone from 4720-26 was perforated with four holes per foot for production on October 5, 1951.

Approved: DEC 18 1951

J. J. Korichak
 State Oil Inspector
 DIRECTOR
 Colorado Oil and Gas Conservation Commission
 1136 Speer Blvd.
 Denver 4, Colorado

Company Trigood Oil Company

Address Box 1689, Casper, Wyoming

By *J. L. Fusselman*
 J. L. Fusselman
 Title Assistant Manager

Submit reports of proposed work, for approval, on this form in Duplicate.

JDM/ib SOI (2); fld; JLF; DF.