

WELL NAME: HASSLER #27, API #: 043-40015, INSP. # 695108636

JAVERNICK OIL
719-275-3040

HASSLER #27

S E S W SEC. 28-20S-69W

FREMONT COUNTY, CO

719-671-3787 OR 911

719-671-3787 OR 911



COLORADO
Energy & Carbon Management
Commission

Department of Natural Resources



PHOTO 2: LOCATION





PHOTO 3: WELLHEAD AND EQUIPMENT



WGS84
±15ft

38.27331, -105.11548

ft
±12ft

5999

°M
±16

SW237



Colorado Oil & Gas Conservation commission
© 14-Sep-23 13:17:09

PHOTO 4: TANK BATTERY/ TANK CONTENT AND CAPACITY NOT POSTED AT TANK BATTERY. POST LABELS/SIGNS PER RULE 605. THIS IS THE 3RD NOTICE FOR THIS CORRECTIVE ACTION, IMMEDIATE ACTION IS REQUIRED SUBMIT FIRR FORM WITH PHOTOS SHOWING TANK CONTENTS AND CAPACITY IMMEDIATELY.



COLORADO
Energy & Carbon Management
Commission
Department of Natural Resources



PHOTO 5: ELECTRIC METER AND BRAKER PANEL



PHOTO 6: Bradenhead inaccessible or not visible (THERE DOES NOT APPEAR TO BE A BRADENHEAD INSTALLED IN WELLHEAD TREE). Install appropriate fittings to allow bradenhead visual inspection as per Rule 419.a.(1), (2). THIS IS THE 3RD NOTICE FOR THIS CORRECTIVE ACTION, IMMEDIATE ACTION IS REQUIRED.



WGS84
±15ft

38.27330, -105.11553

ft
±11ft

5994

°M
±15

SW242



Colorado Oil & Gas Conservation commission
© 14-Sep-23 13:18:04

PHOTO 7: GAUGE HATCH IS NOT LATCHED. Close and seal gauge hatches when not accessing tank per Rule 608.a.(9). 24 HOURS TO ADDRESS.



COLORADO
Energy & Carbon Management
Commission
Department of Natural Resources



PHOTO 8: NO PRESSURE RELIEF VALVE. Tanks will function as sealed and ventless with gas released only through a vapor control system or properly sized pressure relief valve. per Rule 608.a.(9). 24 HOURS TO INSTALL PRESSURE RELIEF VALVE.



PHOTO 9: T-C ANNULUS PLUMBED TO CRUDE OIL TANK BATTERY.



PHOTO 10: SEPARATOR IN LINE WITH 1" T-C ANNULUS SUPPLY LINE TO TANK BATTERY.

WGS84
±15ft

38.27327, -105.11562

ft
±11ft

6002

°M
±15

NE60

Colorado Oil & Gas Conservation Commission
© 14-Sep-23 13:19:16

PHOTO 11: SEPARATOR IN LINE WITH 1" T-C ANNULUS SUPPLY LINE TO TANK BATTERY IS OPEN TO ATMOSPHERE. Tanks will function as sealed and ventless with gas released only through a vapor control system or properly sized pressure relief valve. per Rule 608.a.(9). 24 HOURS TO ADDRESS THIS CORRECTIVE ACTION.



COLORADO
Energy & Carbon Management
Commission
Department of Natural Resources



PHOTO 12: SEPARATOR IN LINE WITH 1" T-C ANNULUS SUPPLY LINE TO TANK BATTERY IS OPEN TO ATMOSPHERE. Tanks will function as sealed and ventless with gas released only through a vapor control system or properly sized pressure relief valve. per Rule 608.a.(9). 24 HOURS TO ADDRESS THIS CORRECTIVE ACTION.



PHOTO 13: UNUSED EQUIPMENT STORED ON LOCATION (EMPTY LIQUID TOTE). REMOVE UNUSED EQUIPMENT PER RULE 606, IF TOTE IS NECESSARY FOR THE OPERATION OF THE WELL IT MUST BE LABELED. CA DATE 10-14-2023.