

RECEIVED

JUL 22 1974

OIL AND GAS CONSERVATION COMMISSION
DEPARTMENT OF NATURAL RESOURCES
OF THE STATE OF COLORADO



file in duplicate for Patented and Federal lands
file in triplicate for State lands.

COLO. OIL & GAS CONS. COM.

5. LEASE DESIGNATION AND SERIAL NO. PATENTED
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER WATER INJECTION WELL

2. NAME OF OPERATOR CHEVRON OIL CO, WESTERN DIVISION

3. ADDRESS OF OPERATOR RANGELY, COLORADO 81648

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface 2996' NSL; 2663' ENL OF SEC. 1, T1N, R102W
At proposed prod. zone SW NE 6th PM

14. PERMIT NO. RDB - 5302

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7. UNIT AGREEMENT NAME RANGELY WEBER SAND

8. FARM OR LEASE NAME CHASE UNIT

9. WELL NO. 1

10. FIELD AND POOL, OR WILDCAT RANGELY WEBER SAND

11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA SEC. 1 T1N R102W

12. COUNTY RIO BLANCO

13. STATE COLO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Date of work AFTER AUGUST 1, 1974

It is proposed to plug and abandon this well as follows:

1. Rig up and pull tubing.
2. Set 100' cement plug through a retainer, set +50' above 7" casing shoe.
3. Set a 2-3 sacks cement plug on top of the retainer.
4. Pump 150 sacks cement down the 7"-surface pipe annulus.
5. Lay a 30' cement plug in the top of the 7" casing.
6. Weld a plate over casing head and install marker.
7. Remove or bury cement pumping unit foundation and "dead men".
8. Clean up all loose pipe, fittings, debris, etc. from location.
9. Scarify non grassy areas and plant seed (8-10#/acre), avoid further disturbance of surface conditions.

DVR	
FJP	
HRM	
JAM	<input checked="" type="checkbox"/>
JJD	<input checked="" type="checkbox"/>
GCH	
OGM	

18. I hereby certify that the foregoing is true and correct.

SIGNED J.A. THOMPSON TITLE UNIT SUPT. DATE 7-19-74

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE DIRECTOR DATE JUL 24 1974

CONDITIONS OF APPROVAL, IF ANY: