



08705716

GAS CONSERVATION COMMISSION
TMENT OF NATURAL RESOURCES
HE STATE OF COLORADO

RECEIVED

MAR 21 1973

Apply for Patented and Federal lands.
File in triplicate for State lands.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | | | |
|--|--|--|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | | 5. LEASE DESIGNATION AND SERIAL NO. | |
| 2. NAME OF OPERATOR CARDINAL PETROLEUM COMPANY | | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | |
| 3. ADDRESS OF OPERATOR Box 1077, Billings, Montana 59103 | | 7. UNIT AGREEMENT NAME | |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface SW SE Sec. 16-2N-55W At proposed prod. zone Same | | 8. FARM OR LEASE NAME State K | |
| 14. PERMIT NO. | | 9. WELL NO. 1 | |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4462' KB | | 10. FIELD AND POOL, OR WILDCAT Zorichak | |
| | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 16-2N-55W | |
| | | 12. COUNTY Morgan | |
| | | 13. STATE Colorado | |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Date of work Completed July 13, 1972

1. Covered perforations with sand. Dropped 10 sack cement plug on top of sand.
2. Cut off 5 $\frac{1}{2}$ ' casing at 3804' and pulled out of hole.
3. Placed 15 sack cement plug at base of surface pipe and 10 sack plug at top of surface pipe.
4. Cut off casing below plow depth and leveled location.

| | |
|-----|---|
| DVR | |
| FJP | ✓ |
| HUM | ✓ |
| JAM | ✓ |
| JJD | ✓ |

Ex Oil Prod.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

R. D. Orr

Production Superintendent

DATE

March 19, 1973

(This space for Federal or State office use)

APPROVED BY

TITLE

DIRECTOR

U. S. & C. COM. REG.

DATE

MAR 22 1973

CONDITIONS OF APPROVAL, IF ANY:



00104616