


|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |

Locate  
Well  
Correctly



OIL & GAS  
CONSERVATION COMMISSION

File in triplicate on Fee and Patented lands and in  
quadruplicate on State and School lands, with  
OFFICE OF DIRECTOR  
OIL AND GAS CONSERVATION COMMISSION,  
STATE OF COLORADO

|      |   |
|------|---|
| AJJ  |   |
| DVR  |   |
| FJK  | 5 |
| OP   |   |
| HH   |   |
| AH   |   |
| JJD  |   |
| FILE |   |

## LOG OF OIL AND GAS WELL



00054981

Field Lee Pool Company McElroy et al  
 County Morgan Address Sherman Plaza #108; 901 Sherman Street  
 Lease Fee #1  
 Well No. 1 Sec. 3 Twp. 2 North Rge. 57 West Meridian 6th PM State or Pat. Pat.  
 Location 330 Ft. (N) of South Line and 1650 Ft. (W) of Sec. 3 line Elevation 4482 DF  
 (Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed E. R. McElroyDate February 7, 1955Title E. R. McElroy

The summary on this page is for the condition of the well as above date.

Commenced drilling October 23, 1950 Finished drilling November 4, 1950

## OIL AND GAS SANDS OR ZONES

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

## IMPORTANT WATER SANDS

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ No. 3, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_

## CASING RECORD

| SIZE    | WT. PER FOOT | MAKE | WHERE LANDED | NO. OF SKS. CEMENT | STOOD HOURS | PRESSURE TEST PSI |
|---------|--------------|------|--------------|--------------------|-------------|-------------------|
| 10 3/4" | 32 pounds    | Used | 132'         | 75                 | 24          | None              |
|         |              |      |              |                    |             |                   |
|         |              |      |              |                    |             |                   |
|         |              |      |              |                    |             |                   |

## COMPLETION DATA

Total Depth 5630 ft. Cable Tools from \_\_\_\_\_ to \_\_\_\_\_ Rotary Tools from top to bottom  
 Casing Perforations (prod. depth) from None to \_\_\_\_\_ ft. No. of holes One  
 Acidized with None gallons. Other physical or chemical treatment of well to induce flow \_\_\_\_\_  
 Shooting Record None

Prod. began None 19\_\_\_\_ Making \_\_\_\_\_ bbls./day of \_\_\_\_\_ A. P. I. Gravity Fluid on \_\_\_\_\_ Pump ☐  
 Tub. Pres. \_\_\_\_\_ lbs./sq. in. Csg. Pres. \_\_\_\_\_ lbs./sq. in. Gas Vol. \_\_\_\_\_ Mcf. Gas Oil Ratio \_\_\_\_\_ Choke. ☐  
 Length Stroke \_\_\_\_\_ in. Strokes per Min. \_\_\_\_\_ Diam. Pump \_\_\_\_\_ in.  
 B. S. & W. \_\_\_\_\_ %. Gas Gravity \_\_\_\_\_ BTU's/Mcf. \_\_\_\_\_ Gals. Gasoline/Mcf. \_\_\_\_\_

## WELL DATA

Indicate (yes or no) whether or not the following information was obtained.

Electrical Log Yes Date 11/4 1950  
 \_\_\_\_\_ Date \_\_\_\_\_ 19\_\_\_\_

Straight Hole Survey No Type \_\_\_\_\_

Other Types of Hole Survey \_\_\_\_\_ Type \_\_\_\_\_

(Note—Any additional data can be shown on reverse side.)

Time Drilling Record 11 Days

Core Analysis Yes Depth 5467-81 to 5481-97

to \_\_\_\_\_

## FORMATION RECORD

Show all formations, especially all sands and character and contents thereof.

| FORMATION       | TOP  | BOTTOM | REMARKS   |
|-----------------|------|--------|---|
| Niobrara        | 4720 |        | Note: Exceedingly poor samples throughout; no core chips or data available. Hole apparently cored 5467-97 but no samples from 5472-97. Core 5467-81 Rec. 7' 10" dark gr slty sh |
| Ft. Hays        | 5016 |        |   |
| Graneros        | 5375 |        |   |
| Cret. SD Zns. 1 | 5464 |        | 1 1/2' tan-gr bentonite, 3' 10" tight, fine ss, hd, some str., gas bubbles, 1' inbd hd gr sh &  |
| Zn. 2           | 5540 |        |   |

(Continue on reverse side)

Core 5481-97 - 4' tight qtzic slat,  
 2' gr slty sh  
 7' blk sh