

Calif, Nash
27-7N-67W



X = Core sample intervals sent to Mr. E. Huelbollen, Barad in Austin for analyses. See correspondence in ^{NW} general file gfh.

BEST IMAGE
AVAILABLE

CORE ANALYSES FROM YOUR NO. 1 A. NASH
New Windsor Field Colorado

SUSSEX SECTION

DEPTH	PERMEABILITY	% POROSITY	% OIL	% WATER	SPECIFIC GRAVITY	
4279.5	Corrected 4290.5	0	9.3	0	147	2.48
4280.5	51.5	0	8.7	0	159	2.47
4281.5	52.5	0	7.6	0	182	2.51
4282.5	53.5	0	9.1	T	169	2.51
4283.5	54.5	T	7.6	0	196	2.49
4284.5	55.5	2.5	PX 6.8	0	35	2.53
4285.5		0.9	10.7	4.8	93	2.55
4286.5		6.6	13.7	3.6	95	2.56
4287.5		2.4	13.4	7.6	92	2.53
4288.5		11.0	14.4	2.5	93	2.57
4289.5	4300.5	0	FX 10.3	5.6	124	2.48
4290.5		4.0	13.9	6.1	96	2.52
4291.5		1.5	10.7	2.5	71	2.49
4292.5		0	6.9	2.3	13.6	2.60
4293.5		1.3	10.3	3.0	113	2.55
4294.5		30	16.7	6.7	72	2.57
4295.5	4306.5	77	19.5	6.8	53	2.63
4296.5		34	17.4	6.0	69	2.56
4297.5		31	18.9	1.4	67	2.59
4298.5		7.5	13.5	1.9	93	2.55
4299.5		43	GX 18.1	4.1	62	2.53
4300.5		39	17.4	1.5	35	2.60
4301.5		T	5.9	T	146	2.46
4302.5		0.9	6.3	T	126	2.47
4303.5	4314.5	T	7.0	T	115	2.49

16.9
67.9
3.9

TOTAL PERMEABILITY-- SUSSEX SECTION-- 292.6

