

OIL AND GAS CONSERVATION COMMISSION  
OF THE STATE OF COLORADO

00226759

## PLUGGING RECORD



## INSTRUCTIONS

Within thirty (30) days after the plugging of any well, the owner or operator thereof shall file this form in duplicate for wells on Patented or Federal lands, and in triplicate for wells on State lands, give a detailed account of the manner in which the abandonment or plugging work was carried out, including the nature and quantities of materials used in plugging and the location and extent (by depths) of the plugs of different materials; records of the amount, size and location (by depths) of casings and junk left in the well; and a detailed statement of the volume and weight of mud fluid used.

Operator The California Company Field New Windsor Wildcat  
Lease Name Paul Ehrlich, et al Well No. 1 County Weld  
Location SW NE Section 26 Township 7N Range 67W Meridian 6th P.M.  
(Quarter Quarter)  
2136 feet from N Section line and 2144 feet from E Section Line  
N or S E or W

TOTAL DEPTH 9132'DATE OF PLUGGING 11/8/57

## DETAILS OF WORK

The well was plugged and abandoned in the following manner:

1. Placed 50 sacks sloset cement interval 8860-9020' (Top Lyons 9037')
2. Placed 50 sacks regular cement interval 4188-4350' (Top Sussex 4312')
3. Placed 100 sacks regular cement interval 270-520' (10 3/4" casing set at 400')
4. Placed 25 sacks regular cement in top of surface casing with marker installed and inscribed per regulations.

AJJ	
DVR	
FJK	
WRS	
HHM	
AH	
JJD	
FILE	

I/we hereby swear (or affirm) that the statements herein made are a full and correct report:

Approved:

Date NOV 15 1957

Director

Company The California Company Date 11/12/57Address P. O. Box 1769, Casper, Wyo Phone No. 2-5303By [Signature] Title Area Supt.  
(Signature)