

Logs Were Run Using Schlumberger MAXIS 500
Depth Logged From: 2,000 ft to 10,000 ft
Logging Unit Number: 5
Date Logged: 5-Jan-2010 to 6-Jan-2010
Thank You For Choosing GO Wireline!

GO Wireline

Stein Frame

Company: Petroleum Development Oman
Well: Stein-1
Field: Stein
Location: Block 6
Country: Sultanate of Oman
Service Order: 1000000000
Job Number: 1000000000
Run Number: 1
Logging Unit Number: 5
Logging Engineer: Mohammed Al Hinai
Witness: Mohammed Al Hinai
Drilling Fluid: Water Based Mud
Density: 1.05 g/cm3
Viscosity: 45 s
Fluid Loss: 5 cc/30min
Max Recorded Temperature: 200 degF
Max Recorded Pressure: 5,000 psi
Bit Size: 8.5 in
Casing Size: 9.625 in
Casing Depth: 2,000 ft
Logged Interval: 2,000 ft to 10,000 ft

Tool	Serial Number	Length	Weight
Gamma Ray	1000000000	10.00 ft	100.00 lb
Resistivity	1000000000	15.00 ft	150.00 lb
Density	1000000000	12.00 ft	120.00 lb
Neutron	1000000000	8.00 ft	80.00 lb
Sonic	1000000000	20.00 ft	200.00 lb
Caliper	1000000000	5.00 ft	50.00 lb
Total		70.00 ft	700.00 lb

GO Wireline

Stein Frame

Company: Petroleum Development Oman
Well: Stein-1
Field: Stein
Location: Block 6
Country: Sultanate of Oman
Service Order: 1000000000
Job Number: 1000000000
Run Number: 1
Logging Unit Number: 5
Logging Engineer: Mohammed Al Hinai
Witness: Mohammed Al Hinai
Drilling Fluid: Water Based Mud
Density: 1.05 g/cm3
Viscosity: 45 s
Fluid Loss: 5 cc/30min
Max Recorded Temperature: 200 degF
Max Recorded Pressure: 5,000 psi
Bit Size: 8.5 in
Casing Size: 9.625 in
Casing Depth: 2,000 ft
Logged Interval: 2,000 ft to 10,000 ft

Tool	Serial Number	Length	Weight
Gamma Ray	1000000000	10.00 ft	100.00 lb
Resistivity	1000000000	15.00 ft	150.00 lb
Density	1000000000	12.00 ft	120.00 lb
Neutron	1000000000	8.00 ft	80.00 lb
Sonic	1000000000	20.00 ft	200.00 lb
Caliper	1000000000	5.00 ft	50.00 lb
Total		70.00 ft	700.00 lb



Repeat Pass

0 PSI

Database File: aristocrat_h14_785_rcbl_cnl_final/aristocrat_h14_785_rcbl_cnl_final.db
Dataset Pathname: Repeat
Presentation Format: rcbl_all_8_2020_1
Dataset Creation: Sat Apr 20 11:12:28 2024
Charted by: Depth in Feet scaled 1:240





Dataset: Aristocrat_H14_785_RCBL_CNL_Final.db: field\well\run1\Main
Total length: 25.15 ft
Total weight: 299.00 lb
O.D.: 4.50 in

Calibration Report

Database File: C:\ProgramData\Warrior\Data\Aristocrat_H14_785_RCBL_CNL_Final\Aristocrat_H14_785_RCBL_CNL_Final.db
Dataset Pathname: Main
Dataset Creation: Sat Apr 20 11:30:25 2024

Compensated Neutron Calibration Report

Type / Serial: CNT27HBL / 120508
Source / Verifier:
Temperature:

SHOP CALIBRATION — Mon Jan 23 12:40:41 2023

Cal Tube	Units
Tank Ratio	SS/LS
Tank Porosity	pu
LS Detector	cps
SS Detector	cps
Tool Ratio	SS/LS
Tool Porosity	PU

Tool Constant =

Field Verifier	SS Detector	LS Detector	Ratio	Porosity

PRE-SURVEY VERIFICATION

SS Detector	LS Detector	Ratio	Porosity

POST-SURVEY VERIFICATION

SS Detector	LS Detector	Ratio	Porosity

Gamma Ray Calibration Report

Serial Number: 2107026
Tool Model: 270 Probe GCT
Performed: Wed Jul 5 11:54:45 2023

Calibrator Value: 200.0 GAPI

Background Reading: 43.9 cps
Calibrator Reading: 289.1 cps

Sensitivity: 0.5680 GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number: 140139_DD1
Tool Model: RBL-DCT

Calibration Casing Diameter: 5.500 in
Calibration Depth: 365.664 ft

Master Calibration, performed Sat Apr 20 10:19:34 2024:

	Raw (v)		Calibrated (mv)		Results		
	Zero	Cal	Zero	Cal	Gain	Offset	
3'	0.010	0.678	0.500	71.921	107.026	-0.616	
CAL	0.742	0.740					
5'	0.016	0.549	0.500	71.921	112.963	-1.360	
SUM							
S1	0.009	0.672	0.000	100.000	150.966	-1.412	
S2	0.018	0.677	0.000	100.000	151.102	-2.367	
S3	0.020	0.678	0.000	100.000	151.926	-2.995	
S4	0.020	0.679	0.000	100.000	151.839	-3.038	
S5	0.020	0.679	0.000	100.000	151.839	-3.038	
S6	0.011	0.686	0.000	100.000	148.140	-1.656	
S7	0.010	0.661	0.000	100.000	149.927	-1.462	
S8	0.013	0.665	0.000	100.000	153.270	-1.923	

Air Zero Calibration, performed Sat Apr 20 10:19:53 2024:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.011	0.000	-0.000
5'	0.014	0.000	0.003
SUM			
S1	0.007	0.000	0.002
S2	0.010	0.000	0.006
S3	0.010	0.000	0.009
S4	0.012	0.000	0.008
S5	0.019	0.000	-0.003
S6	0.019	0.000	-0.009
S7	0.018	0.000	-0.009
S8	0.015	0.000	-0.002

Temperature Calibration Report

Serial Number: 140139_DD1
Tool Model: RBL-DCT
Performed: Fri Nov 10 06:17:51 2023

	Reference	Reading	
Low Reference:	0.00 degF	0.00	degF
High Reference:	1.00 degF	1.00	degF
Gain:	0.90		
Offset:	0.00		
Delta Spacing:	1		

Company	CHEVRON
Well	Aristocrat H14-785
Field	WATTENBERG
County	WELD
State	CO

Country