

OIL AND GAS CONSERVATION COMMISSION
OF THE STATE OF COLORADORECEIVED
SEP 9 - 1963

PLUGGING RECORD

OIL & GAS
CONSERVATION COMMISSION

SCANNED

INSTRUCTIONS

Within thirty (30) days after the plugging of any well, the owner or operator thereof shall file this form in duplicate for wells on Patented or Federal lands, and in triplicate for wells on State lands, give a detailed account of the manner in which the abandonment or plugging work was carried out, including the nature and quantities of materials used in plugging and the location and extent (by depths) of the plugs of different materials; records of the amount, size and location (by depths) of casings and junk left in the well; and a detailed statement of the volume and weight of mud fluid used.

Operator Patrick A. Doheny Field Ranchero Wilcat
Lease Name Fassler Well No. 4 County Washington
Location NW/4 NE/4 Section 32 Township 2N Range 53W Meridian 6th
(Quarter Quarter)
660 feet from N Section line and 1830 feet from E Section Line
N or S E or W

TOTAL DEPTH 4910'DATE OF PLUGGING August 19, 1963

Verbal

DETAILS OF WORK

8-5/8" casing cemented at 132' KB with 110 sacks 50/50 Posmix treated with 2% gel and 3% CaCl₂. Placed 50 sack cement plug from 4850' to 4700', 15 sack cement plug from shoe of surface casing at 132' to 112' and 10 sack cement plug from surface to 20'.

DVR	
WRS	
HHM	✓
JAM	✓
FJP	✓
JJD	
FILE	

Location checked on 11/27/63, OK Jim

I/we hereby swear (or affirm) that the statements herein made are a full and correct report:

Approved:

Date SEP 10 1963

Director

Company Patrick A. Doheny Date Sept. 6, 1963136 El CaminoAddress Beverly Hills, Calif. Phone No. Cr. 63154By G. W. REED (Signature) Title AGENT