



00266841

GAS CONSERVATION COMMISSION THE STATE OF COLORADO

Application for Patented and Federal lands. File in triplicate for State lands.

RECEIVED

JAN 31 1969

COLO. OIL & GAS CONSERV. COMM.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

Form fields 1-15: 1. OIL WELL [X] GAS WELL [] OTHER []; 2. NAME OF OPERATOR: United States Smelting Refining and Mining Company; 3. ADDRESS OF OPERATOR: P.O. Box 1980, Salt Lake City, Utah 84110; 4. LOCATION OF WELL: NE/4 NE/4 Section 2, T 10 N, R 53 W; 5. LEASE DESIGNATION AND SERIAL NO.; 6. IF INDIAN, ALLOTTEE OR TRIBE NAME; 7. UNIT AGREEMENT NAME; 8. FARM OR LEASE NAME: State 1577; 9. WELL NO.: 1-2; 10. FIELD AND POOL, OR WILDCAT: Wildcat; 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA: Sec 2, T 10 N, R 53 W; 14. PERMIT NO.: 68-562; 15. ELEVATIONS: 4382 KB; 17. COUNTY OR PARISH: Logan; 18. STATE: Colorado

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data. NOTICE OF INTENTION TO: TEST WATER SHUT-OFF [], FRACTURE TREAT [], SHOOT OR ACIDIZE [], REPAIR WELL [], (Other) []; PULL OR ALTER CASING [], MULTIPLE COMPLETE [], ABANDON [X], CHANGE PLANS []; SUBSEQUENT REPORT OF: WATER SHUT-OFF [], FRACTURE TREATMENT [], SHOOTING OR ACIDIZING [], (Other) []; REPAIRING WELL [], ALTERING CASING [], ABANDONMENT [X]. (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Date of work January 13, 1969

- 1. Drilled to 5444' KB, had no commercial shows.
2. Called Oil & Gas Conservation Commission & received verbal approval to plug with Bottom Plug Waiver.
3. Loaded hole with heavy mud 5444' to 127' KB bottom of surface casing.
4. Spotted 15 sack cement in bottom of 8-5/8 surface casing at 127' KB.
5. Spotted 10 sack cement plug in top of surface casing.
6. Well P&A.

Table with 2 columns and 5 rows: DVR, FJP, HHM, JAM, JJD. Checkmarks are present in the second column for FJP, HHM, JAM, and JJD.

Signature of George S. Anderson

18. I hereby certify that the foregoing is true and correct. SIGNED: George S. Anderson, Assistant Manager, Oil Operations, DATE: 1-29-69. APPROVED BY: [Signature], DIRECTOR, O & G CONS. COMM., DATE: FEB 4 1969.